

CraneWerks, Inc.
511 Range Line Road, Morristown, IN 46161
Phone: (765) 763-8959 Fax: (765) 763-8960

Inspection and Preventative Maintenance Report (Stationary Hoists)

Customer Name			Contact:	Date:
Address			Job #:	Service #
City	St.	Zip	Inspector:	Item #:
Capacity (Tons):			Lift:	Voltage:
Equipment Description:			Location:	Cust. ID#:
Crane Manufacturer:			Serial #:	Model #:
Main Hoist Manufacturer:			Serial #:	Model #:
Aux. Hoist Manufacturer:			Serial #:	Model #:

Inspection and Preventative Maintenance	Frequent Inspection	Periodic Inspection
---	---------------------	---------------------

Condition Codes:

0= Not Applicable 1= Very Good 2= Good 3= Acceptable 4= Clean & Lubricate 5= Adjustment Required
 6= Fair (Inspect & Review Periodically) 7= Poor (Repair Recommended) 8= Code Violation (Repair Required)
 9= Further Inspection Required X= Unsafe Condition Exists (Tag-out Recommended)

STRUCTURE		CRANE		TROLLEY		Main	Aux	HOIST		Main	Aux
1	Rail:	17	Wheels:	37	Wheels:			54	Limit Switches:		
2	J Bolts/Clips:	18	Pinion:	38	Pinion:			55	Load Brake:		
3	End Stops:	19	Shafts:	39	Shaft:			56	Motor Brake:		
4	Bridge and Runway:	20	Bearings:	40	Bearings:			57	Load Cable / Chain:		
5	Splices:	21	Gear Reducer(s):	41	Reducer/Coupling:			58	Load Hook/ Latch:		
GENERAL		22	Brakes:	42	Drop Lugs/Sweeps:			59	Hook Block:		
		23	Motor/Brushes:	43	Bumpers/Stops:			60	Rope Drum/Anchor		
		24	Controls:	44	Frame & Side Plates:			61	Gear Train:		
		25	Mainline Contactor:	45	Motor/Brushes:			62	Sheaves:		
6	Floor Disconnect:	26	Resistor Soft Start:	46	Motor Brake:			63	Hoist Suspension:		
7	Disconnect Markings:	27	Collectors:	47	Controls:			64	Motor / Brushes:		
8	Warning Labels	28	Bridge Electrification:	48	Resistor Soft Start:			65	Resistors:		
9	Load Markings:	29	Disconnect Switch:	49	Collectors:			66	Controls:		
10	Access Ladder:	30	End Trucks:	50	Lubrication:			67	Lubrication:		
11	Control Station:	31	Drop Lugs/Sweeps:								
12	Control Markings:	32	Bumpers:								
13	Control Cord:	33	End Stops:								
14	Runway Conductors:	34	Cab:	51	Span:			68	Wire Rope Length:		
15	Warning Devices:	35	Foot Walk/Handrail:	52	Runway Length:			69	Wire Rope Diameter:		
16	Remote Controls:	36	Lubrication:	53	NDT Method:			70	Hook Throat Opening:		

Hazardous and Unsafe Conditions-Violations of OSHA General Safety Duty Clause Section 5(a)(1) 1970 OSH ACT

OSHA and ANSI/ASME Code Deficiencies

Recommended Repairs:	Inspector Signature
----------------------	---------------------