



Lineman's Hoists

Ease of Operation
Strength, Precise Control

Series 2000 — Unsurpassed Load Spotting

- Precision Load Control and Spotting — Achieved with friction brake design and fine-tooth pawl. Friction brake allows “micro-inching” when lowering loads.
- Reduced Handle Stroke and 360° Handle Rotation — Allows operator to work in tight spaces.

Extra Measure of Reliability

- Hook Gate Latches — See models below and descriptions on page 3.
- Meets or exceeds minimum 4:1 design factor and all requirements of ASME/ANSI Standard B-30.21. All units tested at 125% of rated load.

SPECIFICATIONS

Series 2000 • Single & Double Line
1000 & 2000 Lbs.

| Model Number | SINGLE LINE | | | DOUBLE LINE | | | Web Strap Length (Ft.) | Handle Length (In.) | Ship Weight (Lbs.) |
|-------------------|-----------------|------------|---------------------------|-----------------|------------|---------------------------|------------------------|---------------------|--------------------|
| | Capacity (Lbs.) | Lift (Ft.) | Hook to Hook (Min.) (In.) | Capacity (Lbs.) | Lift (Ft.) | Hook to Hook (Min.) (in.) | | | |
| 2000A | 1000 | 11 | 17½ | 2000 | 5 | 22 | 12 | 20 | 13¼ |
| * 2000DA | 1000 | 11 | 17½ | 2000 | 5 | 22 | 12 | 20 | 13¼ |
| ** 2000CA | 1000 | 11 | 20½ | 2000 | 5 | 26½ | 12 | 20 | 13¼ |
| *** 200DHA | 1000 | 11 | 19½ | 2000 | 5 | 25 | 12 | 20 | 13¼ |

Series 6000 — Strongest Web Strap Puller Available

- Durable and Rugged — Extra large superior grade webbing with double side plate housing design.
- Positive Load Holding in All Environments — Provided by double interlocking pawl mechanism.
- Extremely Low Handle Effort — Provided by special 4:1 gear reduction.

Extra Measure of Reliability

- Gate Latches — See models below and descriptions on page 3.
- Added Webbing Protection — Wire-form strap guide and special bottom block roller guide web smoothly on to drum.
- Meets or exceeds minimum 4:1 design factor and all requirements of ASME/ANSI Standard B-30.21. All units tested at 125% of rated load.

SPECIFICATIONS

Series 6000 Lineman's Hoist
Double Line - 6000 Lbs.

| Model Number | SINGLE LINE | | | DOUBLE LINE | | | Web Strap Length (Ft.) | Handle Length (In.) | Ship Weight (Lbs.) |
|------------------|-----------------|------------|---------------------------|-----------------|------------|---------------------------|------------------------|---------------------|--------------------|
| | Capacity (Lbs.) | Lift (Ft.) | Hook to Hook (Min.) (In.) | Capacity (Lbs.) | Lift (Ft.) | Hook to Hook (Min.) (in.) | | | |
| 6000A | NA | — | — | 6000 | 5 | 27 | 12 | 30 | 26½ |
| * 6000DA | NA | — | — | 6000 | 5 | 27 | 12 | 30 | 26½ |
| ** 6000CA | NA | — | — | 6000 | 5 | 31½ | 12 | 30 | 26½ |

* Includes Hot Stick Rings on All Hooks, Control Surfaces and Quick Disconnect Shaft.

** Includes Swivel-Type Gate on All Hooks.

*** Includes Hot Stick-Type Gate Latch on All Hooks as well as Hot Stick Rings on All Hooks, Control Surfaces and Quick Disconnect Shaft.